

| BEARING NO | OD | ID | Width | Ball Complement | | Maximum speed | | Weight |
|------------|-------|--------|-------|-----------------|---------|---------------|-------------|--------|
| | D(MM) | d (MM) | B(MM) | NO | Size | Grease (r/mi) | Oil (r/min) | Kg/pcs |
| 62300 | 35 | 10 | 17 | 6 | 7.1440 | 23000 | 27000 | 0.0730 |
| 62301 | 37 | 12 | 17 | 6 | 7.9380 | 20000 | 24000 | 0.0814 |
| 62302 | 42 | 15 | 17 | 7 | 7.9380 | 17000 | 21000 | 0.1050 |
| 62303 | 47 | 17 | 19 | 7 | 8.7310 | 16000 | 190000 | 0.1460 |
| 62304 | 52 | 20 | 21 | 7 | 9.5250 | 14000 | 17000 | 0.1950 |
| 62305 | 62 | 25 | 24 | 7 | 11.5000 | 12000 | 14000 | 0.3060 |
| 62306 | 72 | 30 | 27 | 7 | 12.0000 | 10000 | 12000 | 0.4780 |
| 62307 | 80 | 35 | 31 | 8 | 13.4940 | 8800 | 10000 | 0.6470 |
| 62308 | 90 | 40 | 33 | 8 | 15.0810 | 7800 | 9200 | 0.8850 |
| 62309 | 100 | 45 | 36 | 8 | 17.4620 | 7000 | 8200 | 1.1560 |
| 62310 | 110 | 50 | 40 | 8 | 19.0500 | 6400 | 7500 | 1.4980 |
| 62311 | 120 | 55 | 43 | 8 | 20.6380 | 5800 | 6800 | 1.9180 |
| 62312 | 130 | 60 | 46 | 8 | 22.2250 | 5400 | 6300 | 2.4220 |
| 62313 | 140 | 65 | 48 | 8 | 24.0000 | 4900 | 5800 | |
| 62314 | 150 | 70 | 51 | 8 | 25.4000 | 4600 | 5400 | |
| 62315 | 160 | 75 | 55 | 8 | 26.9000 | 4300 | 5000 | |
| 62316 | 170 | 80 | 58 | 8 | 28.5750 | 4000 | 4700 | |
| 62317 | 180 | 85 | 60 | 8 | 30.1625 | 3800 | 4500 | |
| 62318 | 190 | 90 | 64 | 8 | 31.7500 | 3600 | 4200 | |
| 62319 | 200 | 95 | 67 | 8 | 34.0000 | 3300 | 3900 | |